

AJAX	BASE	CSS	Effects	DOM	Attributes	Manipulation	Traversing
\$get(url)	\$(expr)	background()	hide()	href()	after(html)	add(expr)	
\$get(url, params)	\$(elem)	background(val)	show()	href(val)	after(elem)	add(els)	
\$get(url, callback)	\$(elems)	color()	toggle()	html()	after(elems)	add(el)	
\$get(url, params, callback)	\$(fn)	color(val)		html(val)	append(html)	ancestors()	
\$getIfModified(url)	\$(obj)	css(name)	Animations :	id()	append(elem)	ancestors(expr)	
\$getIfModified(url, params)	\$(expr, context)	css(prop)	animate(params, speed, callback)	id(val)	append(elems)	children()	
\$getIfModified(url, callback)	each(fn)	css(key, value)	fadeIn(speed)	name()	appendTo(expr)	children(expr)	
\$getIfModified(url, params, callback)	eq(pos)	float()	fadeIn(speed, callback)	name(val)	before(html)	contains(str)	
load(url, params, callback)	get()	float(val)	fadeOut(speed)	rel()	before(elem)	end()	
loadIfModified(url, params, callback)	get(num)	height()	fadeOut(speed, callback)	rel(val)	before(elems)	filter(expr)	
	gt(pos)	height(val)	fadeTo(speed, opacity)	src()	clone()	filter(exprs)	
	lengthIn(pos)	left()	fadeTo(speed, opacity, callback)	src(val)	empty()	find(expr)	
	size()	left(val)	hide(speed)	title()	insertAfter(expr)	next()	
		overflow()	hide(speed, callback)	title(val)	insertBefore(expr)	next(expr)	
		overflow(val)	show(speed)	val()	prepend(html)	not(el)	
		position()	show(speed, callback)	val(val)	prepend(elem)	not(expr)	
		position(val)	slideDown(speed)		prepend(elems)	parent()	
		top()	slideDown(speed, callback)		prependTo(expr)	parent(expr)	
		top(val)	slideToggle(speed)		remove()	parents()	
		width()	slideToggle(speed, callback)		remove(expr)	parents(expr)	
		width(val)	slideUp(speed)		wrap(html)	prev()	
			slideUp(speed, callback)		wrap(elem)	prev(expr)	

SAMPLE CODE

```

$(‘p’)
$("#element_id").click(...)
$(".class").click(...)
$(document.getElementById("el")).click(...)
$(document).ready(...)
$(window).load(...)
$(Context).find(...)
$("p",document).size();
$("p[a]").hide();
$("div",document.getElementById("el"))
$xml.responseXML;
$("title",xml.responseXML);

```

Events

bind(type, fn)	keypress(fn)	ondblclick(fn)	resize(fn)	unclick()	unmousedown()
blur(fn)	keyup()	oneerror(fn)	scroll()	unclick(fn)	unmousedown(fn)
<u>Browser</u>	keyup(fn)	onefocus(fn)	scroll(fn)	undblclick()	unmousemove()
error()	load()	onekeydown(fn)	select()	undblclick(fn)	unmousemove(fn)
change(fn)	load(fn)	onekeypress(fn)	select(fn)	unerror()	unmouseout()
click(fn)	<u>Mouse</u>	onekeyup(fn)	submit()	unerror(fn)	unmouseout(fn)
dblclick()	click()	oneload(fn)	submit(fn)	unfocus()	unmouseup()
dblclick(fn)	mousedown()	onemousedown(fn)	toggle(even, odd)	unfocus(fn)	unmouseup(fn)
error(fn)	mousedown(fn)	onemousemove(fn)	trigger(type)	unkeydown()	unresize()
focus()	mousemove()	onemouseout(fn)	User Interface	unkeydown(fn)	unresize(fn)
focus(fn)	mousemove(fn)	onemouseup(fn)	blur()	unkeypress()	unscroll()
<u>Form</u>	mouseout()	oneresize(fn)	unbind()	unkeypress(fn)	unscroll(fn)
change()	mouseout(fn)	onescroll(fn)	unbind(type)	unkeyup()	unselect()
hover(over, out)	mouseup()	oneselect(fn)	unbind(type, fn)	unkeyup(fn)	unselect(fn)
<u>Keyboard</u>	mouseup(fn)	onesubmit(fn)	unblur()	unload()	unsubmit()
keydown()	oneblur(fn)	oneunload(fn)	unblur(fn)	unload()	unsubmit(fn)
keydown(fn)	onechange(fn)	ready(fn)	unchange()	unload(fn)	ununload()
keypress()	oneclick(fn)	resize()	unchange(fn)	unload(fn)	ununload(fn)

JavaScript

```

$.each(obj, fn)
$.extend(obj, prop)
$.grep(array, fn, inv)
$.map(array, fn)
$.merge(a, b)
$.trim(str)

```